

ADVANCE LUBE ENTERPRISE SDN. BHD.

(co. No. 565982-TI HS (M) 3745 PTD 153751, Jalan Berjaya 8, Taman Perindustrian Berjaya, Kempas Lama, 81200 Johor Bahru, Johor. Malaysia.

PRODUCT DATA SHEET

SUPER SPORT 4T SAE 10W-30 API SN JASO MA2

Product Overview:

SUPER SPORT 4T SAE 10W-30 API SN JASO MA2 MOTORCYCLE ENGINE OIL is a PREMIUM engine oil manufactured for four stroke & two stroke engines. Superb for newer motorcycle engines. It improves Load & Friction carrying capability. Reduces stress from daily commutes in start-stop traffic, particularly in hot and humid climates. It offers excellent oil-performance reliability, helping to protect and clean your engine as well as prolong its life. This engine oil is manufactured with high safety measures and quality control according to ISO 9001:2015 standard. Recommended shelf life is 3 to 3½ years, but normally can last for 5 years.

Benefits & Features

- Superb for newer motorcycle engines.
- Quick protection during morning start-up of engines.
- Easy starting especially when the engine is cold due to its lower viscosity & thinner oil.
- Excellent shear stability to dampen vibration and reduce noise.
- Better & improves pick-up power as compared to other lower performance oil.
- Ensures higher engine performance and power.
- Reduces problems associated with oxidation during engine operation.
- Reduces carbon, acid and sludge formations.
- Ensures a smoother, cooler and quieter engine.
- Prevents engine rusts & corrosions.
- Keeps the engine running clean and efficient.
- Saves fuels.

<u>Performance</u>

- API SN JASO MA2
- SAE 10W-30

Typical Physical Properties

Characteristics Method	Unit	Method	Typical Value
Kinematic Viscosity @100°C	cSt	ASTM D445	10.4
Kinematic Viscosity @40°C	cSt	ASTM D445	66.0
Viscosity Index	-	ASTM D2270	145
Specific Gravity @15°C	kg/m³	ASTM D4052	0.878
Flash Point	°C	ASTM D93	>180
Pour Point	°C	ASTM D93	-28
Colour	-	ASTM D1500	Golden Yellow
Appearance	-	Visual	Bright & Clear

Technical Support

For additional technical support or inquiries, please contact our customer service team.