

## PRODUCT DATA SHEET

### ULTRA 4T SAE 10W-40 SN JASO MA2

#### Product Overview:

ULTRA 4T SAE 10W-40 SN JASO MA2 MA 1LITRE is a Premium motorcycle engine oil primarily for newer engines. It is specially formulated for four stroke & two stroke motorcycle engines. It reduces stress from daily commutes in start-stop traffic, particularly in hot and humid climates. It offers excellent oil-performance reliability, helping to protect and clean your engine as well as prolong its life. It is specially designed for all types of motorcycles. It enhances smoothness & comfort in riding. It provides engines with better pick-up power, cleaner & quieter engines for a more enjoyable ride.

Its advanced additive system ensures excellent control over wear due to friction, soot induced wear, high temperature deposits, corrosion, foaming and oxidation stability. This engine oil is manufactured with high safety measures and quality control according to ISO 9001:2015 standard. Recommended shelf life is 3 to 3½ years, but normally can last for 5 years..

#### Benefits & Features

- Excellent for Newer & older motorcycle engines.
- Easier starting when cold due to its lower viscosity & lighter oil.
- Ensures higher engine performance and power.
- Excellent shear stability – to dampen vibration and reduce noise.
- Helps motorcycle to perform better & improves pick-up
- power as compared to other lower performance oil.
- Ensures higher engine performance and power.
- Reduces problems associated with oxidation during engine operation.
- Reduces carbon, acid and sludge formations.
- Ensures smoother, cooler, cleaner and quieter engine.
- Prevents engine rusts & corrosions.

#### Performance

- API SN JASO MA2 MA SAE 10W-40

#### Typical Physical Properties

Characteristics Method	Unit	Method	Typical Value
Kinematic Viscosity @100°C	cSt	ASTM D445	13.80
Kinematic Viscosity @40°C	cSt	ASTM D445	95.0
Viscosity Index	-	ASTM D2270	147
Specific Gravity @15°C	kg/m <sup>3</sup>	ASTM D4052	0.88
Flash Point	°C	ASTM D93	>200
Pour Point	°C	ASTM D93	-30
TBN	mgKOH/g	ASTM D2896	>6.5
Colour	-	ASTM D1500	2.5

#### Technical Support

For additional technical support or inquiries, please contact our customer service team.